Скачать:

➤ Zywall usg 50 user manual

Download:

➤ Zywall usg 50 user manual

.
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
. .
.
. .
. .
. .
. .
. .
. .
. .
.
. .
. .
. .
. .
. .
. .
.
. .

. Zywall usg 50 user manual Go back to the previous page, to see the newly created IKE rule with the destination Dynamic. Если ты все же не хотите занимать место на своем устройстве, Вы всегда можете скачать ее из ManualsBase. Please note that to make sure this policy route applies to all VoIP traffic, including both the SIP signaling and RTP voice datawe need to enable SIP ALG. Concurrent Sessions Per Host to Administrator can adjust this value according to his real network environment. Limit each user s number of sessions Direction: from LAN to Any. Create an SSL application object for the VNC server. ENGLISH 3 Connecting the Hardware Make sure that the power switch on the rear panel is turned off before you make the hardware connections. Add Sub-Class under interface LAN to manage download traffic. The traffic distribution among the two connections: WAN1: 1M WAN2: 0. PRIORITY ACTUAL RATE Yes Yes 1 2 800 kbps 200 kbps Maximize Bandwidth Usage Effect With maximize bandwidth usage enabled, after each server gets its configured rate, the rest of the available bandwidth is divided equally between the two. Setup ZyWALL VPN This page guides us to setup a VPN connection between the WINXP VPN software and ZyWALL router. Add an SSL VPN rule for Tom to access. See the example below: WAN1 free connection bandwidth: 1M WAN2 billing connection bandwidth: 800K Total outbound traffic is 1. ZLD configuration Step 1. Click Open Tunnel to enable it. Since WAN1 has a bandwidth about twice that of WAN2, we can assign the weights to WAN1 and WAN2 as follows: WAN1 Weight: 2 WAN2 Weight: 1 The outbound traffic sessions will be assigned to WAN1 and WAN2 according to their proportional weights. First of all, please make sure Content Filter service is licensed. Port Interface Zone IP Address and DHCP Settings Suggested Use With Default Settings P1 ge1 LAN 192. To prevent any user from consuming too many sessions, we can limit each user s sessions to a specific number. Cannot access Check the cable connection between the ZyWALL and your computer or switch. В вашем браузере отключены файлы cookies. Enable Session Limit, and set Default Session per Host to Administrator can adjust this value according to his real network environment. Zywall usg 50 user manual Enable Maximize Bandwidth Usage. Warnings tell you about things that could harm you or your device. So the network administrator needs to make policies to prevent these undesirable types of browsing. Configure the trunk name and add the two interfaces: PPPoE for Active and 3G for Passive mode. Fill in the Phase-1 configuration. Click the Add button to add a rule. Send all User Guide-related comments, questions or suggestions for improvement to the following address, or use e-mail instead. Note: Notes tell you other important information for example, other things you may need to configure or helpful tips or recommendations. USG ZyWALL provides network administrators with flexible ways of implementing WAN load balancing according to their demands.